SRU SOLUTIONS DYNAWAVE® REVERSE JET SCRUBBER

99.9+% SULFUR REMOVAL AT THE LOWEST COST AND WITH THE HIGHEST RELIABILITY



Claus Sulfur Recovery Units (SRU) are found in various industries, such as refineries, natural gas processing plants, chemical plants, and coal gasification facilities.

The Claus process is widely used to recover sulfur from H_2S containing gas streams. However, a Claus SRU can typically recover only 95 – 98% of the sulfur present. Many times, Tail Gas Treatment Units (*TGTU*) are installed downstream of a Claus SRU to increase the overall sulfur recovery to 99.0 – 99.9% in order to comply with local environmental regulations. These TGTUs may include

amine-based TGTUs (SCOT type), cold-bed sub-dewpoint processes (SULFREEN,* CBA, etc.), or direct oxidation type processes (SUPERCLAUS,* EUROCLAUS,* etc.).

RECOVERY EFFICIENCY

Depending on the sulfur recovery efficiency provided by the SRU/TGTU combination, local environmental regulations for SO₂ emissions may be met normally. However, operations during start-up, shutdown and malfunction-upsets may require further treatment downstream of the TGTU, or treatment as an alternate/redundant operation to the TGTU. This is where the DynaWave[®] wet gas scrubbing technology can provide reliable and worry-free operations, and guaranteed SO₂ removal to meet environmental regulations and good neighbor objectives.

WORRY-FREE, SIMPLE AND ROBUST DESIGN

DynaWave[°] is a unique open bore, reverse jet scrubber that utilizes "Froth Zone" technology to perform desulfurization in a wet gas environment. This proven technology will reduce total installed cost, simplify operations and deliver over 99.9+% sulfur removal.

Contact MECS[®] for more information regarding environmental performance enhancements for your specific SRU application.

FEATURES AND BENEFITS:

EMISSIONS REDUCTION

- 99.9+% sulfur removal
- Less than 25 ppm SO₂ emissions
- Meets environmental and "good neighbor" objectives

OPERATIONS AND RELIABILITY

- Low capital cost
- Less operating cost
- Meets start-up, shutdown and
- malfunction emissions regulationsAlternate/redundant operation to
- the TGTU
- Simple controls, reliable operation

TECHNOLOGY

- Field proven
- Added flexibility:
 - Handles high SO₂ inlet
 - Can compensate for and complement SRU performance
 - Handles SRU tail gas if TGTU is shutdown or bypassed
 - Excellent polishing technology for
 - very low SO₂ levels (10 ppm)
- Over 300 DynaWave® Scrubbers installed worldwide



Copyright© 2012. E. I. du Pont de Nemours and Company. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™, DynaWave® and MECS® are registered trademarks of DuPont or its affiliates.

The miracles of science

HOW A REVERSE JET WET GAS SCRUBBER WORKS

SRU SOLUTIONS

The DynaWave[®] Reverse Jet Scrubber is an open duct in which scrubbing liquid is injected, through a non-restrictive reverse jet nozzle, counter current to the dirty inlet gas. Liquid collides with down flowing gas to create the "Froth Zone," a region of extreme turbulence with a high rate of mass transfer. The clean, water saturated gas continues through the scrubber vessel to mist removal devices. The liquid reverses direction and returns to the vessel sump for recycle back to the reverse jet nozzle. For SRU applications, DynaWave[®] is installed after the incinerator and before the stack.

DYNAWAVE® REVERSE JET SCRUBBER

NUMEROUS APPLICATIONS:

CLAUS SRU

- CLAUS Incinerator DynaWave®
- CLAUS TGTU Incinerator DynaWave[®]

OTHER SULFUR APPLICATIONS

- H₂S Scrubbing
- Sulfur Pit or Storage Vents
- Flare Gas H₂S Scrubber
- Fuel Gas Treater
- Coal Gasification

PROVEN PERFORMANCE

- Over 300 wet scrubbing systems installed worldwide
- Flow rates from 1,000 to over 1,000,000 ACFM (1700 to over 1,700,000 Nm3/hr)
- SO₂ levels up to 200,000 ppm
- Can handle inlet temperatures
- above 2,200° F *(1,200° C)*

TYPICAL DYNAWAVE® REVERSE JET SCRUBBER

CLEAN DIRTY GAS OUT GASIN **SEE HOW IT WORKS** View a Quicktime[®] video on the MECS[®] web site at: www.dynawavescrubber.com PATH OF GAS SRU SOLUTIONS FROTH ZONE REVERSE JET NOZZLE REAGENT MAKE-UP **OXIDATION AIR** (OPTIONAL) **REVERSE JET NOZZLE** EFFLUENT



www.mecsglobal.com

North America

MECS Headquarters Chesterfield, Missouri 63017 USA Tel: +1-314-275 5700 northamerica@mecsglobal.com

Europe/Africa

Brussels, Belgium MECS Europe/Africa BVBA Tel: +32-2-658 2620 europe-africa@mecsglobal.com

Milan, Italy

MECS Europe/Africa BVBA Phone: +39-02-8969 0658 italy@mecsglobal.com

Johannesburg, South Africa

MECS Europe/Africa BVBA Tel: +27-11-708 9860 southafrica@mecsglobal.com

Asia/Pacific

Hong Kong, China MECS Far East Limited Tel: +852-2734 5388 hongkong@mecsglobal.com

Shanghai, China

MECS Chemical Plants Equipment (Shanghai) Co., Ltd Tel: +86-21-6182 1111 shanghai@mecsglobal.com

Mumbai, India

MECS India Private Ltd. Tel: +91-22-6774 9500 india@mecsglobal.com

South America

Barueri, Sao Paulo, Brazil MECS, Inc. DuPont Sustainable Solutions Tel: +55-11-4166 8000 brazil@mecsglobal.com